



TECHNICAL DATASHEET

BRUSH-ON SEAM SEALER

ART. NO: #135.695 (1L)

BRUSH-ON SEAM SEALER is a synthetic, rubber-based sealant that can be applied directly onto seams and joints with a paintbrush. Creates an elastic, temperature resistant layer that can be painted over and is impervious to water and mineral spirits.

FEATURES

- ✓ Permanently flexible/will not crack
- ✓ Paintable
- ✓ Holds a perfect brush mark to match OEM seams
- ✓ Adheres to both wet or dry surfaces
- ✓ Hot and cold resistant (-25°C to 80°C)
- ✓ Will not sink or sag
- ✓ Minimal shrinkage
- ✓ Can be used on bare metal or primed/painted surfaces

APPLICATION

Ideal for waterproof sealing of all "lap" and "flange" seams and joints, particularly when after-market body parts and covering trim are installed in places that will later be painted. Can also serve as body protection for weld seams.

COMPATIBLE TOPCOATS

- ✓ Solvent borne base coat
- ✓ 2K & 1K single stage paint
- ✓ Primer & sealers

N.B. In the case of waterborne base coats, a sealer must be applied.

CONDITIONS OF USE AND CONFORMITY

The before mentioned technical data and information, especially the recommendations for applying and using our products, are based on our current knowledge and experience when applied under normal conditions. In practice, the materials, surfaces or site conditions are so different that no warranty regarding the working results or liability, arising out of any relationship, can be inferred neither from this information nor from a verbal consultation, except we are charged with intent or gross negligence. In this case the user is obliged to prove that he has informed us about all points required for a proper and promising judgment in writing, in time and completely. Patent rights of any third party are to be observed. Furthermore, our general sales and delivery Terms and Conditions and the latest Technical Data Sheet, which should be demanded, apply.

HEALTH & SAFETY

See Safety Data Sheet and labels for additional safety information and handling instructions. Directions for handling and waste disposal are in our Material Safety Data Sheet and the specifications of the Employers Liability Insurance Association for the chemical industry. Wear appropriate PPE such as eye and skin protection. In the event of injury, see first aid procedures on SDS. Always observe all applicable precautions and follow good safety and hygiene practices.

PRODUCT DATA

Color: Grey

Specific gravity: Approximately 1.5 kg/l

Recommended Coverage: 1.2 kg/m²

Drying Time (20°C at 65% RH): 12 hours

Shelf Life: 6 months in original container

Package: 1L

Number per case: 6

Safety Data Sheet (SDS) is available on our website



TECHNICAL DATASHEET



HANDLING

MIXING

1. Make sure product is at room temperature 20°C (70°F) before mixing.
2. Stir the seam sealer with a stir-stick until it is a uniform consistency.



PREPARATION

1. Clean the repair area with a degreaser ensuring that the surface is clean, dry and free of grease and wax.
2. Lightly scuff the surface in order to ensure maximum adhesion.
3. Use an air gun to blow away any dust and dirt from the seam.



APPLICATION

1. Using a using a putty spreader or brush, apply enough material to completely cover desired area.
2. Re-brush entire seam for uniformity.
3. Allow to dry completely before painting.



DRY TIMES

Full Cure : 12 Hours

Dry to Touch / Paintable: 20 - 30 min @ 20°C (70°F) with a R.H. of 65%