



TECHNICAL DATASHEET

CLEAR COAT SPRAY

ART. NO: #126.025 (400ml)

CLEAR COAT SPRAY is a transparent, acrylic-based enamel designed for quick spot repairs of nearly all surfaces including wood, metal and acrylic paint. Not only is this sprayable clear coat high gloss, durable and weather resistant, but it has a fast drying time and is easy to use.

FEATURES

- ✓ High gloss finish
- ✓ Acrylic-based
- ✓ Transparent
- ✓ Weather and wear resistant
- ✓ Fast drying
- ✓ Suitable for most surfaces

APPLICATION

All-purpose acrylic clear coat mono-component for spot repairs. Quick drying, easy and universal application, good gloss and resistance to UV.

CONDITIONS OF USE AND CONFORMITY

The before mentioned technical data and information, especially the recommendations for applying and using our products, are based on our current knowledge and experience when applied under normal conditions. In practice, the materials, surfaces or site conditions are so different that no warranty regarding the working results or liability, arising out of any relationship, can be inferred neither from this information nor from a verbal consultation, except we are charged with intent or gross negligence. In this case the user is obliged to prove that he has informed us about all points required for a proper and promising judgment in writing, in time and completely. Patent rights of any third party are to be observed. Furthermore, our general sales and delivery Terms and Conditions and the latest Technical Data Sheet, which should be demanded, apply.

HEALTH & SAFETY

See Safety Data Sheet and labels for additional safety information and handling instructions. Directions for handling and waste disposal are in our Material Safety Data Sheet and the specifications of the Employers Liability Insurance Association for the chemical industry. Wear appropriate PPE such as eye and skin protection. In the event of injury, see first aid procedures on SDS. Always observe all applicable precautions and follow good safety and hygiene practices.

PRODUCT DATA

Nature: Acrylic

Color: Transparent

Theoretical Coverage: 400 ml = 1 - 2 m²

Grade of Gloss: High gloss

Shelf Life: 12 - 18 months

Package: 400 ml

Number per case: 6

Safety Data Sheet (SDS) is available on our website



TECHNICAL DATASHEET

CAUTION

CONTENTS UNDER PRESSURE. DO NOT STORE AT TEMPERATURES ABOVE 50°C. NOT SUITABLE FOR USE ON PURE WHITE SURFACES.



HANDLING

MIXING

1. Make sure product is at room temperature 72°F (22.2°C) before mixing.
2. Shake can vigorously for 2 - 3 minutes before use. Spray to test before applying.



PREPARATION

Clean the surface, removing all traces of dirt, grease, oil and rust. Ensure that the surface is completely dry before application.




APPLICATION

1. Apply and let base coat color dry as per recommended procedures.
2. Spray in steady, even strokes approximately 20 - 30 cm (8 - 12") away from the surface using even up-and-down and side-to-side movements.
3. Apply 2 - 3 thin coats until the surface is completely covered leaving 4 - 7 minutes between coats.



RECOMMENDED THICKNESS

Wet: 75µm (3 mils)
Dry: 35µm (1.5 mils)



FLASH TIME

Between coats: 4 - 7 minutes



DRY TIMES

Dust Free: 3 minutes
Air Dry: 60 minutes @ 70°F (20°C)
Full Cure: 2 - 3 hours @ 70° F (20°C)



AFTER USE

Turn can upside down and spray until valve is clean in order to prevent the valve from clogging between uses.