



TECHNICAL DATASHEET

COPPER SPRAY

ART. NO: #135.170 (400 ml)

COPPER SPRAY is a professional lubricant designed for machines and engine components exposed to high thermal stress. Has excellent adhesion and its high copper content allows for a thermal resistance between - 30°C to + 1100°C. Anti-seize and prevents corrosion and damage from wear, oxidation, water and salts.

FEATURES

- ✓ Easy to use aerosol application
- ✓ High thermal resistance
- ✓ Protects against corrosion
- ✓ Multi-purpose use

APPLICATION

Ideal for use on brake parts, hinges, battery poles, heating pipes, bolts on exhaust pipes and wire connections.

CONDITIONS OF USE AND CONFORMITY

The before mentioned technical data and information, especially the recommendations for applying and using our products, are based on our current knowledge and experience when applied under normal conditions. In practice, the materials, surfaces or site conditions are so different that no warranty regarding the working results or liability, arising out of any relationship, can be inferred neither from this information nor from a verbal consultation, except we are charged with intent or gross negligence. In this case the user is obliged to prove that he has informed us about all points required for a proper and promising judgment in writing, in time and completely. Patent rights of any third party are to be observed. Furthermore, our general sales and delivery Terms and Conditions and the latest Technical Data Sheet, which should be demanded, apply.

HEALTH & SAFETY

See Safety Data Sheet and labels for additional safety information and handling instructions. Directions for handling and waste disposal are in our Material Safety Data Sheet and the specifications of the Employers Liability Insurance Association for the chemical industry. Wear appropriate PPE such as eye and skin protection. In the event of injury, see first aid procedures on SDS. Always observe all applicable precautions and follow good safety and hygiene practices.

CAUTION

PRESSURIZED CONTAINER. KEEP OUT OF DIRECT SUNLIGHT AND TEMPERATURES EXCEEDING 50°C. EXTREMELY FLAMMABLE. PROTECT SURROUNDING OBJECTS FROM OVER-SPRAY.

HANDLING

1. Bring can to room temperature with an ideal operating temperature between 5°C to 30°C.
2. Ensure surface is clean, dry and free of any grease, dust or dirt.
3. Shake can vigorously for 2 - 3 minutes before use.
4. Spray evenly onto the parts to be lubricated, shaking can occasionally during use.
5. Allow solvent to evaporate (approximately 1 minute) for optimal lubrication.

N.B. Screws and nuts should be sprayed before being screwed into place.

PRODUCT DATA

Nature: EP grease and copper particles

Color: Copper

Temperature Resistance: - 30°C to +1100°C

Storage: 5 years in unopened container

Package: 400 ml

Number per case: 12

Safety Data Sheet (SDS) is available on our website