



TECHNICAL DATASHEET

CW-480 BLONDE

ART. NO:	SIZE:	QUANTITY:
#134.805	¾" (18mm x 55m)	48 rolls/case
#134.806	1½" (36mm x 55m)	24 rolls/case
#134.807	2" (48mm x 55m)	24 rolls/case

CW-480 BLONDE is a waterproof masking tape designed for a wide variety of applications including car repair, indoor and outdoor painting, building and decoration, and even industrial purposes. Compatible with most common paints and lacquers, not only is this tape engineered to resist bleed through, but it offers excellent adhesion to rough surfaces while remaining easy to remove. Highly resistant to UV light, water and moisture, this professional grade masking tape is also temperature resistant up to 90°C (194°F).

FEATURES

- ✓ *Waterproof*
- ✓ *Temperature resistant*
- ✓ *Easy to remove*
- ✓ *Hand tearable*
- ✓ *No adhesive residue*
- ✓ *Good adhesion to rough surfaces*
- ✓ *Compatible with most traditional paints and lacquers*
- ✓ *Will not break during removal*
- ✓ *UV resistant*

APPLICATION

Ideal for use in a wide variety of applications including car repair and wall painting on building and construction sites. Can also be used in outdoor conditions.

CONDITIONS OF USE AND CONFORMITY

Product shelf life and storage: 12 months. Suggested storage temperature shall range from 15°C to 25°C with max. relative humidity of 65%. Material shall be stored away from heat sources and possibly kept in original package, avoiding light exposure as well. When temperatures are lower than suggested, it is always required to recondition the tape at normal temperature before use. This information is given to the best of Carworx's knowledge. Values are typical and do not constitute a specification. Customers are required to do their own testing under their working conditions for their intended application. Any liability arising in respect of our products will be limited to the value of those products charged to the customer excluding any consequential loss.

PRODUCT DATA

Color: Blonde

Backing: Waterproof saturated crepe paper

Adhesive: Natural rubber & resin based

Total Thickness: 0.145 mm (5.7 mils)

Adhesion to Steel: 4.8N/25 mm (17 oz./in.)

Tensile Strength MD: 90N/25 mm (20 lbs./in.)

Elongation at break: 8%

Temperature Resistance: 90°C (194°F) for 30 min.