

TECHNICAL DATASHEET

CW-800 AQUAWORX

ART. NO:	SIZE:	QUANTITY:
#134.770	³ ⁄4" (18mm x 55m)	48 rolls/case
#134.771	1" (25mm x 55m)	32 rolls/case
#134.772	1½" (36mm x 55m)	24 rolls/case
#134.773	2" (48mm x 55m)	24 rolls/case
#134.774	3" (75mm x 55m)	12 rolls/case

CW-800 AQUAWORX is a high visibility turquoise tape designed for car repair applications. Its unique color allows for high visibility and easy removal, all the while ensuring excellent adhesion to a variety of surfaces. Compatible with most paints and lacquers, this high performance masking tape is also temperature resistant up to 90°C (194°F).

FEATURES

- ✓ Temperature resistant
- ✓ Easy to remove
- ✓ Hand tearable
- ✓ Good adhesion to even and uneven surfaces
- ✓ Compatible with most traditional paints and lacquers
- ✓ Will not break during removal
- ✓ UV resistant

APPLICATION

Ideal for a wide variety of car repair applications when temperatures do not exceed 90°C (194°F).

CONDITIONS OF USE AND CONFORMITY

Product shelf life and storage: 12 months. Suggested storage temperature shall range from 15°C to 25°C with max. relative humidity of 65%. Material shall be stored away from heat sources and possibly kept in original package, avoiding light exposure as well. When temperatures are lower than suggested, it is always required to recondition the tape at normal temperature before use. This information is given to the best of Carworx's knowledge. Values are typical and do not constitute a specification. Customers are required to do their own testing under their working conditions for their intended application. Any liability arising in respect of our products will be limited to the value of those products charged to the customer excluding any consequential loss.

PRODUCT DATA

Color: Turquoise Backing: Saturated crepe paper Adhesive: Natural rubber & resin based Total Thickness: 0.130 mm (5.1 mils) Adhesion to Steel: 4.3N/25 mm (15 oz./in.) Tensile Strength MD: 85N/25 mm (19 lbs./in.) Elongation at break: 8% Temperature Resistance: 90°C (194°F) for 30 min.