



TECHNICAL DATASHEET

CW-900 BLUE

ART. NO:	SIZE:	QUANTITY:
#134.860	¾" (18mm x 55m)	48 rolls/case
#134.862	1½" (36mm x 55m)	24 rolls/case
#134.863	2" (48mm x 55m)	24 rolls/case

CW-900 BLUE is a waterproof masking tape designed specifically for the automotive sector and paint shops. Compatible with both solvent and water based paints, not only is this tape engineered to resist bleed through, but its thin profile provides a fine-line paint edge, making it ideal for a wide variety of car repair applications and painting purposes. Easy to remove and made with solvent based adhesive, this high performance masking tape is also temperature resistant up to 90°C (194°F).

FEATURES

- ✓ *Waterproof*
- ✓ *Temperature resistant*
- ✓ *Easy to remove*
- ✓ *Hand tearable*
- ✓ *No adhesive residue*
- ✓ *Good adhesion to even and uneven surfaces*
- ✓ *Compatible with most traditional paints and lacquers*
- ✓ *Will not break during removal*
- ✓ *UV resistant*

APPLICATION

Ideal for a wide variety of car repair applications and painting purposes. Can also be used for general wall painting on buildings as well as for various applications in the industrial sector.

CONDITIONS OF USE AND CONFORMITY

Product shelf life and storage: 12 months. Suggested storage temperature shall range from 15°C to 25°C with max. relative humidity of 65%. Material shall be stored away from heat sources and possibly kept in original package, avoiding light exposure as well. When temperatures are lower than suggested, it is always required to recondition the tape at normal temperature before use. This information is given to the best of Carworx's knowledge. Values are typical and do not constitute a specification. Customers are required to do their own testing under their working conditions for their intended application. Any liability arising in respect of our products will be limited to the value of those products charged to the customer excluding any consequential loss.

PRODUCT DATA

- Color:** Blue
- Backing:** 63 g/m² waterproof saturated crepe paper
- Adhesive:** Natural rubber & resin based
- Total Thickness:** 0.130 mm (5.1 mils)
- Adhesion to Steel:** 4.8N/25 mm (17 oz./in.)
- Tensile Strength MD:** 90N/25 mm (20 lbs./in.)
- Elongation at break:** 8%
- Temperature Resistance:** 90°C (194°F) for 30 min.