



TECHNICAL DATASHEET

CW-950 RED

ART. NO:	SIZE:	QUANTITY:
#134.880	¾" (18mm x 55m)	48 rolls/case
#134.881	1" (25mm x 55m)	32 rolls/case
#134.882	1½" (36mm x 55m)	24 rolls/case
#134.883	2" (48mm x 55m)	24 rolls/case
#134.884	3" (75mm x 55m)	12 rolls/case

CW-950 RED is a professional grade masking tape designed for the automotive sector. Not only is it waterproof, but its thin profile creates a fine-line paint edge, making it perfect for car repair applications and painting purposes. Compatible with most solvent and water based paints, this high performance masking tape is also temperature resistant up to 90°C (194°F).

FEATURES

- ✓ *Waterproof*
- ✓ *Temperature resistant*
- ✓ *No adhesive residue*
- ✓ *Good adhesion to even and uneven surfaces*
- ✓ *Compatible with most traditional paints and lacquers*
- ✓ *Will not break during removal*
- ✓ *UV resistant*

APPLICATION

Ideal for use in high moisture conditions such as during wet sanding or when painting. Can also be used for general wall painting on buildings as well as for various applications in the industrial sector.

CONDITIONS OF USE AND CONFORMITY

Product shelf life and storage: 12 months. Suggested storage temperature shall range from 15°C to 25°C with max. relative humidity of 65%. Material shall be stored away from heat sources and possibly kept in original package, avoiding light exposure as well. When temperatures are lower than suggested, it is always required to recondition the tape at normal temperature before use. This information is given to the best of Carworx's knowledge. Values are typical and do not constitute a specification. Customers are required to do their own testing under their working conditions for their intended application. Any liability arising in respect of our products will be limited to the value of those products charged to the customer excluding any consequential loss.

PRODUCT DATA

- Color:** Red
- Backing:** Water resistant saturated crepe paper
- Adhesive:** Natural rubber & resin based
- Total Thickness:** 0.135 mm (5.3 mils)
- Adhesion to Steel:** 4.8N/25 mm (17 oz./in.)
- Tensile Strength MD:** 90N/25 mm (20 lbs./in.)
- Elongation at break:** 8%
- Temperature Resistance:** 90°C (194°F)