

TECHNICAL DATASHEET

FINE LINE TAPE

ART. NO:	SIZE:	QUANTITY:
#140.082	1/ ₁₆ " (1.5mm x 55m)	10 rolls/case
#140.083	1/8" (3mm x 55m)	10 rolls/case
#140.084	1/4" (6mm x 55m)	10 rolls/case
#140.085	²³ / ₆₄ " (9mm x 55m)	10 rolls/case
#140.086	½" (12mm x 55m)	10 rolls/case
#140.087	³ / ₄ " (18mm x 55m)	10 rolls/case

FINE LINE TAPE is a multi-purpose vinyl masking tape engineered for custom design painting. Resistant to both high temperatures and temperature changes, this high performance tape creates flawless lines and superior color separation without leaving behind any adhesive residue.

FEATURES

- ✓ Easy handling
- ✓ Ideal for masking and lettering
- ✓ Resistant to moisture
- ✓ Resists baking temperatures up to 150°C (302°F)
- ✓ Creates clear lines and color separations
- ✓ Cadmium free
- ✓ Made with synthetic rubber adhesives

APPLICATION

Ideal for custom painting and detailing during both painting and drying processes.

CONDITIONS OF USE AND CONFORMITY

Product shelf life and storage: 12 months. Suggested storage temperature shall range from 15°C to 25°C with max. relative humidity of 65%. Material shall be stored away from heat sources and possibly kept in original package, avoiding light exposure as well. When temperatures are lower than suggested, it is always required to recondition the tape at normal temperature before use. This information is given to the best of Carworx's knowledge. Values are typical and do not constitute a specification. Customers are required to do their own testing under their working conditions for their intended application. Any liability arising in respect of our products will be limited to the value of those products charged to the customer excluding any consequential loss.

PRODUCT DATA

Color: Orange

Backing: Plasticized PVC film **Adhesive:** Synthetic rubber

Total Thickness: 0.125 mm (4.9 mils)

Peel Adhesion: 2.6N/10 mm (.57 lbs./in.)

Tensile Strength MD: 27N/10 mm (5.97 lbs./in.)

Elongation at break: 100%

Temperature Resistance: Between -30°C (-86°F)

and 150°C (302°F)