

TECHNICAL DATASHEET

MASKING FILM

ART. NO:	SIZE:	QUANTITY:
#134.800	4m x 150m	1 roll/box
#134.801	4.8m x 100m	1 roll/box

MASKING FILM is a semi-transparent masking film designed for quick masking of large surface components prior to painting. Statically charged with good paint adhesion, making it easy to position the product on the surface as desired. Extremely high wear resistance and temperature stable up to 110°C (230°F).

FEATURES

- ✓ Corona treated, holding onto paint mist and dust while protecting the surface from contamination
- ✓ Statically charged for better adhesion
- √ Easy application
- ✓ Environmentally friendly
- ✓ Saves on time and costs
- ✓ Packaging doubles as a dispenser
- ✓ Accelerates masking process

APPLICATION

Ideal for quick masking of large scale areas or smaller parts, particularly during automotive painting processes. Can also be used in the industrial sector or at construction sites for quick and easy protection.

N.B. It is crucial that the surface being covered is clean and completely dry before using.

CONDITIONS OF USE AND CONFORMITY

Product shelf life and storage: unlimited if stored in temperatures less than 40°C with max. relative humidity of 65%. max. relative humidity of 65%. Material shall be stored away from heat sources and possibly kept in original package, avoiding light exposure as well. When temperatures are lower than suggested, it is always required to recondition the tape at normal temperature before use. This information is given to the best of Carworx's knowledge. Values are typical and do not constitute a specification. Customers are required to do their own testing under their working conditions for their intended application. Any liability arising in respect of our products will be limited to the value of those products charged to the customer excluding any consequential loss.

PRODUCT DATA

Color: Semi-transparent

Film Type: HDPE

Film Thickness: 0.01mm
Film Treatment: Corona

Shelf Life: Unlimited if stored > 40°C (>104°F)

Temperature Resistance (short periods): 110°C

(230°F)