

MULTI MOUNTING TAPE

ART. NO:	SIZE	E	QUANTITY:
#125.711	1⁄4"	(6mm x 10m)	10 rolls/case
#125.712	3/8""	(9mm x 10m)	10 rolls/case
#125.713	1⁄2"	(12mm x 10m)	10 rolls/case
#125.720	3⁄4"	(19mm x 10m)	10 rolls/case
#125.725	1"	(25mm x 10m)	10 rolls/case
#125.726	2"	(50mm x 10m)	10 rolls/case

MULTI MOUNTING TAPE is a double-sided, foam back tape designed for vibration resistant bonding. Characteristics include high adhesion and excellent resistance to UV light, weathering and aging.

FEATURES

- ✓ Highly conformable
- ✓ Hand tearable
- ✓ Easy to use
- ✓ UV resistant
- Resistant to weathering and aging
- ✓ High adhesion and elongation
- ✓ Performs well on even and uneven surfaces

APPLICATION

Ideal for fixing decoration profiles, emblems, plates and edge lining strips in the automotive repair sector.

CONDITIONS OF USE AND CONFORMITY

Product shelf life and storage: 12 months. Suggested storage temperature shall range from 15°C to 25°C with max. relative humidity of 65%. Material shall be stored away from heat sources and possibly kept in original package, avoiding light exposure as well. When temperatures are lower than suggested, it is always required to recondition the tape at normal temperature before use. This information is given to the best of Carworx's knowledge. Values are typical and do not constitute a specification. Customers are required to do their own testing under their working conditions for their intended application. Any liability arising in respect of our products will be limited to the value of those products charged to the customer excluding any consequential loss.

PRODUCT DATA

Color: Green liner with black foam backing Backing: 1.0 mm black 6PCF PE foam Adhesive: Solvent based acrylic Liner: 3 mil green polyolefin Total Thickness: 1.0 mm (40 mils) Tack: 20 Peel Adhesion: 1.4 kg / 25 mm Shear Strength (25°C): Over 24hrs with 1.0 kg loading 2 stainless steel plates on 25 mm x 25 mm Temperature Resistance (24h): 80°C (176°F) Service Temperature: -40°C to 100°C (-104°F to 212°F)