



TECHNICAL DATASHEET

OPTIMAL FAST WAX

ART. NO: #120.105.1 (1L), #120.105.2 (1G)

OPTIMAL FAST WAX is a super high gloss polish with made with Nano Technology that is designed for extended wax protection and repelling dirt. Suitable for a wide variety of applications and compatible with almost all modern paint surfaces, this polish delivers a deep, wet look that exceeds other conventional polishes in terms of durability and shine. Low chalk formula minimizes rubber and plastic staining as well as dusting problems.

FEATURES

- ✓ Produces a superb, high gloss finish
- ✓ Compatible with most paint surfaces
- ✓ Designed as a wipe on - wipe off polish for easy application
- ✓ Delivers a deep, wet look
- ✓ Extra durable
- ✓ No dusting problems

APPLICATION

Suitable for automotive, marine and aerospace applications. Fully tested to ensure compatibility with all modern paint finishes including HS and ceramic clear coats.

RECOMMENDED BUFFING PAD

Use with our microfiber polishing cloth or black foam polishing pad.

CONDITIONS OF USE AND CONFORMITY

The before mentioned technical data and information, especially the recommendations for applying and using our products, are based on our current knowledge and experience when applied under normal conditions. In practice, the materials, surfaces or site conditions are so different that no warranty regarding the working results or liability, arising out of any relationship, can be inferred neither from this information nor from a verbal consultation, except we are charged with intent or gross negligence. In this case the user is obliged to prove that he has informed us about all points required for a proper and promising judgment in writing, in time and completely. Patent rights of any third party are to be observed. Furthermore, our general sales and delivery Terms and Conditions and the latest Technical Data Sheet, which should be demanded, apply.

HEALTH & SAFETY

See Safety Data Sheet and labels for additional safety information and handling instructions. Directions for handling and waste disposal are in our Material Safety Data Sheet and the specifications of the Employers Liability Insurance Association for the chemical industry. Wear appropriate PPE such as eye and skin protection. In the event of injury, see first aid procedures on SDS. Always observe all applicable precautions and follow good safety and hygiene practices.

PRODUCT DATA

Nature: Blend of carnauba wax, non-volatile silicones, polishing aids, non-aromatic solvents, perfume, dye and water

Color: White

pH: 10

Shelf Life: 2 years in unopened container

Package: 1L / 1G

Number per case: 6 (1L) / 4 (1G)

Safety Data Sheet (SDS) is available on our website



TECHNICAL DATASHEET

CAUTION

PROTECT FROM FREEZING. STORE AT AN AMBIENT TEMPERATURE. DO NOT APPLY IN DIRECT SUNLIGHT. SHAKE WELL BEFORE USE. LIKE WITH ANY OTHER WAX, AVOID COATING RUBBER TRIM AND TEXTURED PLASTIC SURFACES.



HANDLING

APPLICATION

1. Shake well before use.
2. Clean surface so that it is free from any dirt or dust. Do not apply in direct sunlight.
3. Apply OPTIMUM FAST WAX sparingly to the clean, cool surface with a soft polishing cloth or foam pad using a buffer at a polishing speed of 800 - 1000 RPM. For optimal results, use our MICROFIBER CLOTH or BLACK FOAM PAD.
4. Allow product to haze, then buff to shine until desired finish is achieved.

N.B. Provides protection lasting from 30 - 90 days.