



TECHNICAL DATASHEET

SILVER WHEEL SPRAY

ART. NO: #126.021 (400ml)

SILVER WHEEL SPRAY is a fast drying, acrylic based aerosol designed to protect your wheels from corrosion while making them look brand new. Highly resistant to abrasives and will not rub or flake off.

FEATURES

- ✓ Fast drying
- ✓ Can be used on all wheel types and sizes
- ✓ Protects from corrosion
- ✓ Long lasting
- ✓ Metallic finish restores color and shine

APPLICATION

Ideal for use on steel wheel rims and other automotive wheels.

CONDITIONS OF USE AND CONFORMITY

The before mentioned technical data and information, especially the recommendations for applying and using our products, are based on our current knowledge and experience when applied under normal conditions. In practice, the materials, surfaces or site conditions are so different that no warranty regarding the working results or liability, arising out of any relationship, can be inferred neither from this information nor from a verbal consultation, except we are charged with intent or gross negligence. In this case the user is obliged to prove that he has informed us about all points required for a proper and promising judgment in writing, in time and completely. Patent rights of any third party are to be observed. Furthermore, our general sales and delivery Terms and Conditions and the latest Technical Data Sheet, which should be demanded, apply.

HEALTH & SAFETY

See Safety Data Sheet and labels for additional safety information and handling instructions. Directions for handling and waste disposal are in our Material Safety Data Sheet and the specifications of the Employers Liability Insurance Association for the chemical industry. Wear appropriate PPE such as eye and skin protection. In the event of injury, see first aid procedures on SDS. Always observe all applicable precautions and follow good safety and hygiene practices.

CAUTION

CONTENTS UNDER PRESSURE. DO NOT STORE AT TEMPERATURES ABOVE 50°C.

HANDLING

1. Clean the wheels thoroughly, removing all traces of rust, grease, oil and dirt.
2. Shake can vigorously for at least 2 - 3 minutes before use. Spray to test before applying.
3. Spray in steady, even strokes approximately 25 - 30 cm away from the wheel surface. Use even up-and-down and side-to-side movements.
4. Apply in several thin coats until wheel is covered.
5. After use, turn can upside down and spray until valve is clean in order to prevent the valve from clogging between uses.

VOC INFORMATION

Category	Metallic Coating
Reactivity MIR	0.66 g O ₃ /g of product

PRODUCT DATA

Color: Silver

Coverage: 400 ml = 4 - 5 standard wheel rims

Drying Time (20°C): 15 - 20 minutes

Cure Time (20°C): 60 minutes

Shelf Life: 2 years in original packaging

Package: 400 ml

Number per case: 6

Safety Data Sheet (SDS) is available on our website