



TECHNICAL DATASHEET

SPRAY PAINT TRIM BLACK

ART. NO: #126.027 (400ml)

TRIM BLACK is a fast drying acrylic spray paint designed for all types of paint work, from repairing damaged surfaces to paint finishing. Fast drying, polishable and weather resistant, with excellent adhesion to nearly all surfaces.

FEATURES

- ✓ Fast drying
- ✓ Matte finish
- ✓ Weather resistant
- ✓ Can be polished
- ✓ Excellent adhesion to most surfaces

APPLICATION

All-purpose spray paint designed for any kind of paint work.

CONDITIONS OF USE AND CONFORMITY

The before mentioned technical data and information, especially the recommendations for applying and using our products, are based on our current knowledge and experience when applied under normal conditions. In practice, the materials, surfaces or site conditions are so different that no warranty regarding the working results or liability, arising out of any relationship, can be inferred neither from this information nor from a verbal consultation, except we are charged with intent or gross negligence. In this case the user is obliged to prove that he has informed us about all points required for a proper and promising judgment in writing, in time and completely. Patent rights of any third party are to be observed. Furthermore, our general sales and delivery Terms and Conditions and the latest Technical Data Sheet, which should be demanded, apply.

HEALTH & SAFETY

See Safety Data Sheet and labels for additional safety information and handling instructions. Directions for handling and waste disposal are in our Material Safety Data Sheet and the specifications of the Employers Liability Insurance Association for the chemical industry. Wear appropriate PPE such as eye and skin protection. In the event of injury, see first aid procedures on SDS. Always observe all applicable precautions and follow good safety and hygiene practices.

CAUTION

CONTENTS UNDER PRESSURE. DO NOT STORE AT TEMPERATURES ABOVE 50°C.

HANDLING PREPARATION

1. Clean the surface, removing all traces of dirt, grease, oil and rust. Any rust present in pores must be treated with a rust-removing agent.
2. Sand any uneven areas and spray a wash primer if no filler is needed. Otherwise, apply filler as per manufacturer's recommendations.
3. Once the filler has dried completely, wet-sand using P1000 sandpaper until smooth.

APPLICATION

1. Clean and mask repair site before painting. If a large surface is being sprayed, it is recommended to mask off all seams and corners of the car body.
2. Shake can vigorously for 2 - 3 minutes before use. Spray to test before applying.
3. Spray in steady, even strokes approximately 25 - 30 cm away from the surface, applying several thin coats with a 3 - 5 minute flash-off time between coats.
5. After use, turn can upside down and spray until valve is clean in order to prevent the valve from clogging between uses.

VOC INFORMATION

Category	Flat Coating
Reactivity MIR	0.73 g O ₃ /g of product

PRODUCT DATA

Color: Black

Theoretical Coverage: 400 ml = 1.3 m²

Dust Free (20°C): 10 minutes

Tack Dry (20°C): 15 minutes

Re-coat Time (20°C): 15 minutes

Dry to touch (20°C): 50 minutes

Grade of Gloss: Matte

Shelf Life: 36 months stored at 20°C (70°F)

Package: 400 ml

Number per case: 6

Safety Data Sheet (SDS) is available on our website



TECHNICAL DATASHEET

SPRAY PAINT WHITE GLOSS

ART. NO: #126.053 (400ml)

WHITE GLOSS is a fast drying acrylic spray paint designed for all types of paint work, from repairing damaged surfaces to paint finishing. Fast drying, polishable and weather resistant, with excellent adhesion to nearly all surfaces.

FEATURES

- ✓ Fast drying
- ✓ High gloss finish
- ✓ Weather resistant
- ✓ Can be polished
- ✓ Excellent adhesion to most surfaces

APPLICATION

All-purpose spray paint designed for any kind of paint work.

CONDITIONS OF USE AND CONFORMITY

The before mentioned technical data and information, especially the recommendations for applying and using our products, are based on our current knowledge and experience when applied under normal conditions. In practice, the materials, surfaces or site conditions are so different that no warranty regarding the working results or liability, arising out of any relationship, can be inferred neither from this information nor from a verbal consultation, except we are charged with intent or gross negligence. In this case the user is obliged to prove that he has informed us about all points required for a proper and promising judgment in writing, in time and completely. Patent rights of any third party are to be observed. Furthermore, our general sales and delivery Terms and Conditions and the latest Technical Data Sheet, which should be demanded, apply.

HEALTH & SAFETY

See Safety Data Sheet and labels for additional safety information and handling instructions. Directions for handling and waste disposal are in our Material Safety Data Sheet and the specifications of the Employers Liability Insurance Association for the chemical industry. Wear appropriate PPE such as eye and skin protection. In the event of injury, see first aid procedures on SDS. Always observe all applicable precautions and follow good safety and hygiene practices.

CAUTION

CONTENTS UNDER PRESSURE. DO NOT STORE AT TEMPERATURES ABOVE 50°C.

HANDLING PREPARATION

1. Clean the surface, removing all traces of dirt, grease, oil and rust. Any rust present in pores must be treated with a rust-removing agent.
2. Sand any uneven areas and spray a wash primer if no filler is needed. Otherwise, apply filler as per manufacturer's recommendations.
3. Once the filler has dried completely, wet-sand using P1000 sandpaper until smooth.

APPLICATION

1. Clean and mask repair site before painting. If a large surface is being sprayed, it is recommended to mask off all seams and corners of the car body.
2. Shake can vigorously for 2 - 3 minutes before use. Spray to test before applying.
3. Spray in steady, even strokes approximately 25 - 30 cm away from the surface, applying several thin coats with a 3 - 5 minute flash-off time between coats.
5. After use, turn can upside down and spray until valve is clean in order to prevent the valve from clogging between uses.

VOC INFORMATION

VOC INFORMATION	
Category	Non-flat Coating
Reactivity MIR	0.73 g O ₂ /g of product

PRODUCT DATA

Color: White

Theoretical Coverage: 400 ml = 1.3 m²

Dust Free (20°C): 10 minutes

Tack Dry (20°C): 15 minutes

Re-coat Time (20°C): 15 minutes

Dry to touch (20°C): 50 minutes

Grade of Gloss: Glossy

Shelf Life: 36 months stored at 20°C (70°F)

Package: 400 ml

Number per case: 6

Safety Data Sheet (SDS) is available on our website